

Fortron Racing Oil Fully Synthetic SAE 0W30 API SN,SM/CF ACEA A3-D3



Fortron Racing Oil Fully Synthetic SAE 0W30 API SN,SM/CF

For Benzine, Gasoline, Diesel Engine

FORTRON FULLY SYNTHETIC 0W-30 RACING OIL is recommended for use in high-performance turbocharged, multi-cam, multi-valve, naturally aspirated, 4-cylinder and larger race and highly modified street engines. Advanced Group IV Poly Alpha Olefin (PAO) base oils provide shear stable protection from cold start-up to extreme temperatures.

FORTRON FULLY SYNTHETIC 0W-30 RACING OIL provides the ultimate protection at extreme operating temperatures and enhanced protection for all fuel types. Ideal for vehicles using E85 and other high-performance fuels.



SUMMARY OF BENEFITS

- Outstanding thermal and oxidation stability
- High anti-wear protection package
- Suitable for race and highly modified street engines
- Durable shear stable formula
- High temperature protection
- Advanced Group IV Poly Alpha Olefin (PAO)

PERFORMANCE

- API SN/SM/CF
- ACEA A3-02

Properties	UNIT	METHOD	0W-30
APPEARANCE	-	VISUAL	Bright & Clear
Denisty @ 30° C	Kg/l	ASTM D4052	0.8337
VISCOSITY 40° C	cSt	ASTM D445	59.49
VISCOSITY 100° C	cSt	ASTM D445	10.89
VISCOSITY INDEX	-	ASTM D2270	177
CCS @-35° C	cPs	ASTM D5293	5967
TOTAL BASE NUMBER	mgKOH/g	ASTM D2896	8.40

